

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einZA Kompaktlasur, esche

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einZA Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einZA.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

This product does not meet the classification criteria given in the Regulation (EC) No 1272/2008 (CLP).

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms

-

Signal word

-

Hazard statement(s)

-

Hazard statements (EU)

EUH210 Safety data sheet available on request.

Precautionary statement(s)

-

Labelling information

The labelling (EU hazard statements) meets the criteria of annex II of Directive (EC) Nr. 1272/2008 (CLP).

2.3 Other hazards

PBT assessment

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

The components of this product are not considered to be a PBT.
vPvB assessment
The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

| No | Substance name | | Additional information | |
|----|--|-------------------------------------|------------------------|-----|
| | CAS / EC / Index / REACH no | Classification (EC) 1272/2008 (CLP) | Concentration | % |
| 1 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | |
| | - 918-481-9 - 01-2119457273-39 | Asp. Tox. 1; H304 EUH066 | >= 50.00 - < 70.00 | wt% |
| 2 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | | | |
| | 13463-67-7 236-675-5 022-006-00-2 01-2119489379-17 | Carc. 2; H351i | < 0.50 | wt% |

Full Text for all H-phrases and EUH-phrases: pls. see section 16

| No | Note | Specific concentration limits | M-factor (acute) | M-factor (chronic) |
|----|----------|-------------------------------|------------------|--------------------|
| 2 | V, W, 10 | - | - | - |

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

| No | Route, target organ, concrete effect |
|----|--------------------------------------|
| 2 | H351i inhalational; -; - |

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

| No | Substance name | CAS no. | EC no. |
|---|--|------------|-------------------|
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| List of approved workplace exposure limits (WELs) / EH40 | | | |
| Titanium dioxide | | | |
| total inhalable dust | | | |
| | WEL long-term (8-hr TWA reference period) | 10 | mg/m ³ |
| List of approved workplace exposure limits (WELs) / EH40 | | | |
| Titanium dioxide | | | |
| respirable dust | | | |
| | WEL long-term (8-hr TWA reference period) | 4 | mg/m ³ |

DNEL, DMEL and PNEC values

DNEL values (worker)

| No | Substance name | | | CAS / EC no |
|----|--|---------------------|--------|-------------------------|
| | Route of exposure | Exposure time | Effect | Value |
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | | | 13463-67-7 236-675-5 |
| | inhalative | Long term (chronic) | local | 1.25 mg/m ³ |

DNEL value (consumer)

| No | Substance name | | | CAS / EC no |
|----|--|---------------------|--------|-------------------------|
| | Route of exposure | Exposure time | Effect | Value |
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | | | 13463-67-7 236-675-5 |
| | inhalative | Long term (chronic) | local | 210 µg/m ³ |

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

| | | | |
|----------------------|---|-----|-----|
| Appropriate Material | In case of short-term contact / splash protection: nitrile rubber | | |
| Material thickness | > | 0.4 | mm |
| Breakthrough time | > | 120 | min |
| Appropriate Material | In case of prolonged exposure: nitrile rubber | | |
| Material thickness | > | 0.4 | mm |
| Breakthrough time | > | 480 | min |

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | | |
|--------------------------------------|------------|-----|-----|
| State of aggregation | | | |
| liquid | | | |
| Form | | | |
| liquid | | | |
| Colour | | | |
| according to product name | | | |
| Odour | | | |
| characteristic | | | |
| pH value | | | |
| No data available | | | |
| Boiling point / boiling range | | | |
| Value | appr. | 100 | °C |
| Melting point/freezing point | | | |
| No data available | | | |
| Decomposition temperature | | | |
| No data available | | | |
| Flash point | | | |
| Value | >= | 62 | °C |
| Method | closed cup | | |
| Ignition temperature | | | |
| No data available | | | |
| Oxidising properties | | | |
| Not applicable | | | |
| Flammability | | | |
| Not applicable | | | |
| Lower explosion limit | | | |
| No data available | | | |
| Upper explosion limit | | | |
| No data available | | | |
| Vapour pressure | | | |
| Value | < | 100 | hPa |
| Reference temperature | | 50 | °C |

Trade name: einza Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

| Relative vapour density | |
|-------------------------|--|
| No data available | |

| Relative density | |
|-------------------|--|
| No data available | |

| Density | |
|-----------------------|-------------------------------|
| Value | 0.84 - 0.89 g/cm ³ |
| Reference temperature | 20 °C |
| Method | DIN 51757 |

| Solubility in water | |
|---------------------|------------|
| Comments | immiscible |

| Solubility | |
|-------------------|--|
| No data available | |

| Partition coefficient n-octanol/water (log value) | | | |
|---|--|-------------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | 918-481-9 |
| | log Pow | 3.17 - 7.22 | |
| | Method | QSAR | |
| | Source | ECHA | |
| 2 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| | Not applicable | | |
| | Source | ECHA | |

| Kinematic viscosity | |
|-----------------------|--------------------|
| Value | 33 - 37 sec |
| Reference temperature | 20 °C |
| Method | DIN EN 2431 (4 mm) |

| Solvent separation test | |
|-------------------------|--|
| Not applicable | |

| Particle characteristics | |
|--------------------------|--|
| No data available | |

9.2 Other information

| Other information | |
|--------------------|--|
| No data available. | |

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

| Acute oral toxicity | | | |
|-----------------------------------|--|------------|------------------|
| No | Substance name | CAS no. | EC no. |
| 1 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | 918-481-9 |
| LD50 | > | 15000 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| 2 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| LD50 | > | 2000 | mg/kg bodyweight |
| Species | rat | | |
| Method | OECD 401 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| Acute dermal toxicity | | | |
| No data available | | | |
| Acute inhalational toxicity | | | |
| No | Substance name | CAS no. | EC no. |
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| LC50 | | 5.09 | mg/l |
| Duration of exposure | | 4 | h |
| State of aggregation | Dust | | |
| Species | rat | | |
| Method | OECD 403 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| Skin corrosion/irritation | | | |
| No | Substance name | CAS no. | EC no. |
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Species | rabbit | | |
| Method | OECD 404 | | |
| Source | ECHA | | |
| Evaluation | non-irritant | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| Serious eye damage/irritation | | | |
| No | Substance name | CAS no. | EC no. |
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Species | rabbit | | |
| Method | OECD 405 | | |
| Source | ECHA | | |
| Evaluation | non-irritant | | |
| Evaluation/classification | Based on available data, the classification criteria are not met. | | |
| Respiratory or skin sensitisation | | | |
| No | Substance name | CAS no. | EC no. |

Trade name: einzA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

| | | | |
|---------------------------|---|---|------------------|
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Route of exposure | | Skin | |
| Species | | mouse | |
| Method | | OECD 429 | |
| Source | | ECHA | |
| Evaluation | | non-sensitizing | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

Germ cell mutagenicity

| No | Substance name | CAS no. | EC no. |
|---------------------------|--|---|------------------|
| 1 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | 918-481-9 |
| Type of examination | | in vitro gene mutation study in bacteria | |
| Species | | S. typhimurium TA 1535, TA 1537, TA 98 and TA 100S. typhimurium TA 1535, TA 1537, TA 98, TA 100, TA 102 | |
| Method | | OECD 471 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |
| Route of exposure | | oral | |
| Type of examination | | In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus | |
| Species | | mouse | |
| Method | | OECD 474 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

| | | | |
|---------------------------|---|---|------------------|
| 2 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Type of examination | | In vitro mammalian cytogenicity | |
| Method | | OECD 487 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |
| Route of exposure | | oral | |
| Type of examination | | In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus | |
| Species | | rat | |
| Method | | OECD 474 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

Reproduction toxicity

| No | Substance name | CAS no. | EC no. |
|---------------------------|---|---|------------------|
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Route of exposure | | oral | |
| NOAEL | | ≥ 1000 mg/kg bw/d | |
| Type of examination | | Reproductive studies - one generation | |
| Species | | rat | |
| Method | | OECD 443 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |
| Route of exposure | | oral | |
| NOAEL | | 1000 mg/kg bw/d | |
| Type of examination | | Prenatal Developmental Toxicity Study | |
| Species | | rat | |
| Method | | OECD 414 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

Carcinogenicity

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

| No | Substance name | CAS no. | EC no. |
|---------------------------|--|---|------------|
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Route of exposure | | oral | |
| NOEL | | 7500 | mg/kg bw/d |
| Species | | mouse | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

STOT - single exposure

No data available

STOT - repeated exposure

| No | Substance name | CAS no. | EC no. |
|---------------------------|--|---|------------|
| 1 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | 918-481-9 |
| Route of exposure | | oral | |
| NOAEL | | >= 500 | mg/kg bw/d |
| Species | | rat | |
| Method | | OECD 408 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |
| 2 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Route of exposure | | oral | |
| NOAEL | | > 962 | mg/kg bw/d |
| Species | | rat | |
| Method | | OECD 408 | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |
| Route of exposure | | inhalational | |
| Species | | rat | |
| Source | | ECHA | |
| Evaluation/classification | | Based on available data, the classification criteria are not met. | |

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity****Toxicity to fish (acute)**

No data available

Trade name: einzA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

| Toxicity to fish (chronic) | |
|----------------------------|--|
| No data available | |

| Toxicity to Daphnia (acute) | |
|-----------------------------|--|
| No data available | |

| Toxicity to Daphnia (chronic) | |
|-------------------------------|--|
| No data available | |

| Toxicity to algae (acute) | | | |
|---------------------------|--|------------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| EC50 | > | 100 | mg/l |
| Duration of exposure | | 72 | h |
| Species | Raphidocelis subcapitata | | |
| Method | OECD 201 | | |
| Source | ECHA | | |
| Evaluation/classification | Based on the available data, the classification criteria are not met. | | |

| Toxicity to algae (chronic) | |
|-----------------------------|--|
| No data available | |

| Bacteria toxicity | |
|-------------------|--|
| No data available | |

12.2 Persistence and degradability

| Biodegradability | | | |
|------------------|--|------------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Source | ECHA | | |
| Evaluation | Not applicable for inorganic substances. | | |

12.3 Bioaccumulative potential

| Partition coefficient n-octanol/water (log value) | | | |
|---|--|------------|-----------|
| No | Substance name | CAS no. | EC no. |
| 1 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | - | 918-481-9 |
| log Pow | 3.17 | - | 7.22 |
| Method | QSAR | | |
| Source | ECHA | | |
| 2 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 |
| Not applicable | | | |
| Source | ECHA | | |

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

| Results of PBT and vPvB assessment | |
|------------------------------------|---|
| PBT assessment | The components of this product are not considered to be a PBT. |
| vPvB assessment | The components of this product are not considered to be a vPvB. |

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

Other information

Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

| No | Substance name | CAS no. | EC no. | No |
|----|---------------------------|----------|-----------|----|
| 1 | 2-(2-butoxyethoxy)ethanol | 112-34-5 | 203-961-6 | 75 |

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

| | | | | |
|---|--|------------|-----------|----|
| 2 | 2-methylpentane-2,4-diol | 107-41-5 | 203-489-0 | 75 |
| 3 | titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | 13463-67-7 | 236-675-5 | 75 |

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 58.63 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : f, type: lb = 700 g/l
 Max. VOC content (limit value) of the product in its ready for use condition = < 700 g/l

National regulations**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066 Repeated exposure may cause skin dryness or cracking.
 H304 May be fatal if swallowed and enters airways.
 H351i Suspected of causing cancer by inhalation.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

V If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

W It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.
 This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

1 The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

Trade name: einZA Kompaktlasur, esche

Product no.: 6140630

Current version : 5.3.0, issued: 03.07.2023

Replaced version: 5.2.0, issued: 25.11.2021

Region: GB

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653791