

Trade name: einza Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einza Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

decorative paints/finishes

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

einza Farben GmbH & Co KG

Junkersstraße 13

30179 Hannover

Telephone no. +49 (0)511 67490-0

Fax no. +49 (0)511 67490-20

e-mail info@einza.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411

Eye Dam. 1; H318

Flam. Liq. 3; H226

Skin Irrit. 2; H315

Skin Sens. 1; H317

STOT SE 3; H335

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS05



GHS07



GHS09

Signal word

Danger

Hazardous component(s) to be indicated on label:

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight > 700 - < 1100)
 Hydrocarbons, C9, aromatics
 butan-1-ol

Hazard statement(s)

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statement(s)

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/eye protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
- P391 Collect spillage.
- P405 Store locked up.
- P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

PBT assessment
 The components of this product are not considered to be a PBT.
 vPvB assessment
 The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight > 700 - < 1100)			
	25068-38-6 500-033-5 - -	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 10.00 - < 25.00	wt%
2	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]			
	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351i	>= 10.00 - < 25.00	wt%
3	Hydrocarbons, C9, aromatics		pls. refer to footnote (2)	

EU safety data sheet

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

	64742-95-6 918-668-5 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066	>= 10.00 - < 25.00	wt%
4	xylene			
	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Acute Tox. 4; H332 Aquatic Chronic 3; H412	>= 5.00 - < 10.00	wt%
5	butan-1-ol			
	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Acute Tox. 4; H302 Eye Dam. 1; H318 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT SE 3; H335 STOT SE 3; H336	< 5.00	wt%
6	2-methoxy-1-methylethyl acetate			
	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	< 5.00	wt%
7	zinc oxide			
	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2.50 - < 25.00	wt%
8	ethylbenzene			
	100-41-4 202-849-4 601-023-00-4 -	Acute Tox. 4; H332 Flam. Liq. 2; H225 Asp. Tox. 1; H304 STOT RE 2; H373 Aquatic Chronic 3; H412	< 2.50	wt%
9	trizinc bis(orthophosphate)			
	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

(2) According to the latest state of knowledge and applying the criteria set out in annex I to Regulation (EC) No 1272/2008, the aforementioned classification is required. This classification goes beyond the classification set out in table 3, Annex VI to Regulation (CE) No 1272/2008.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	V, W, 10	-	-	-
3	P	-	-	-
7	-	-	M = 1	M = 1

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
2	H351i inhalational; -; -
8	H373 inhalational; hearing; -

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
	List of approved workplace exposure limits (WELs) / EH40		
	Titanium dioxide		
	total inhalable dust		
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
	List of approved workplace exposure limits (WELs) / EH40		
	Titanium dioxide		
	respirable dust		
	WEL long-term (8-hr TWA reference period)	4	mg/m ³
2	xylene	1330-20-7	215-535-7
	2000/39/EC		
	Xylene, mixed isomers, pure		
	WEL short-term (15 min reference period)	442	mg/m ³ 100 ppm
	WEL long-term (8-hr TWA reference period)	221	mg/m ³ 50 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	Xylene, o-, m-, p- or mixed isomers		

EU safety data sheet



Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

	WEL short-term (15 min reference period)	441	mg/m ³	100	ppm
	WEL long-term (8-hr TWA reference period)	220	mg/m ³	50	ppm
	Comments	Sk,BMGV			
3	butan-1-ol	71-36-3		200-751-6	
List of approved workplace exposure limits (WELs) / EH40					
Butan-1-ol					
	WEL short-term (15 min reference period)	154	mg/m ³	50	ppm
	Comments	Sk			
4	2-methoxy-1-methylethyl acetate	108-65-6		203-603-9	
List of approved workplace exposure limits (WELs) / EH40					
1-Methoxypropylacetate					
	WEL short-term (15 min reference period)	548	mg/m ³	100	ppm
	WEL long-term (8-hr TWA reference period)	274	mg/m ³	50	ppm
	Comments	Sk			
2000/39/EC					
2-Methoxy-1-methylethylacetate					
	WEL short-term (15 min reference period)	550	mg/m ³	100	ppm
	WEL long-term (8-hr TWA reference period)	275	mg/m ³	50	ppm
	Skin resorption / sensibilisation	Skin			
5	ethylbenzene	100-41-4		202-849-4	
2000/39/EC					
Ethylbenzene					
	WEL short-term (15 min reference period)	884	mg/m ³	200	ppm
	WEL long-term (8-hr TWA reference period)	442	mg/m ³	100	ppm
	Skin resorption / sensibilisation	Skin			
List of approved workplace exposure limits (WELs) / EH40					
Ethylbenzene					
	WEL short-term (15 min reference period)	552	mg/m ³	125	ppm
	WEL long-term (8-hr TWA reference period)	441	mg/m ³	100	ppm
	Comments	Sk			

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]			13463-67-7	
				236-675-5	
	inhalative	Long term (chronic)	local	1.25	mg/m ³
2	Hydrocarbons, C9, aromatics			64742-95-6	
				918-668-5	
	dermal	Long term (chronic)	systemic	12.5	mg/kg/day
	inhalative	Long term (chronic)	systemic	151	mg/m ³
3	xylene			1330-20-7	
				215-535-7	
	dermal	Long term (chronic)		180	mg/kg/day
	inhalative	Short term (acute)		289	mg/m ³
	inhalative	Long term (chronic)		77	mg/m ³
4	butan-1-ol			71-36-3	
				200-751-6	
	inhalative	Long term (chronic)	local	310	mg/m ³
5	2-methoxy-1-methylethyl acetate			108-65-6	
				203-603-9	
	dermal	Long term (chronic)	systemic	796	mg/kg/day
	inhalative	Long term (chronic)	systemic	275	mg/m ³
	inhalative	Short term (acute)	local	550	mg/m ³
6	zinc oxide			1314-13-2	
				215-222-5	
	dermal	Long term (chronic)	systemic	83	mg/kg/day
	with reference to: Zn				
	Comments: insoluble				

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

inhalative	Long term (chronic)	systemic	5	mg/m ³
with reference to: Zn Comments: insoluble				
inhalative	Long term (chronic)	local	0.5	mg/m ³
with reference to: Zn Comments: insoluble				

DNEL value (consumer)

No	Substance name	CAS / EC no		
	Route of exposure	Exposure time	Effect	Value
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7 236-675-5		
	inhalative	Long term (chronic)	local	210 µg/m ³
2	Hydrocarbons, C9, aromatics	64742-95-6 918-668-5		
	oral	Long term (chronic)	systemic	7.5 mg/kg/day
	dermal	Long term (chronic)	systemic	7.5 mg/kg/day
	inhalative	Long term (chronic)	systemic	32 mg/m ³
3	xylene	1330-20-7 215-535-7		
	oral	Long term (chronic)		1.6 mg/kg/day
	dermal	Long term (chronic)		108 mg/kg/day
	inhalative	Short term (acut)		174 mg/m ³
	inhalative	Long term (chronic)		14.8 mg/m ³
4	butan-1-ol	71-36-3 200-751-6		
	oral	Long term (chronic)	systemic	1.562 mg/kg/day
	dermal	Long term (chronic)	systemic	3.125 mg/kg/day
	inhalative	Long term (chronic)	systemic	55.357 mg/m ³
	inhalative	Long term (chronic)	local	155 mg/m ³
5	2-methoxy-1-methylethyl acetate	108-65-6 203-603-9		
	oral	Long term (chronic)	systemic	36 mg/kg/day
	oral	Short term (acut)	systemic	500 mg/kg/day
	dermal	Long term (chronic)	systemic	320 mg/kg/day
	inhalative	Long term (chronic)	systemic	33 mg/m ³
	inhalative	Long term (chronic)	local	33 mg/m ³
6	zinc oxide	1314-13-2 215-222-5		
	oral	Long term (chronic)	systemic	0.83 mg/kg/day
	with reference to: Zn Comments: insoluble			
	dermal	Long term (chronic)	systemic	83 mg/kg/day
	with reference to: Zn Comments: insoluble			
	inhalative	Long term (chronic)	systemic	2.5 mg/m ³
	with reference to: Zn Comments: insoluble			

PNEC values

No	Substance name	CAS / EC no		
	ecological compartment	Type	Value	
1	xylene	1330-20-7 215-535-7		
	water	fresh water	0.327	mg/L
	water	marine water	0.327	mg/L
	water	fresh water sediment	12.46	mg/kg
	water	marine water sediment	12.46	mg/kg
	soil	-	2.31	mg/kg
	sewage treatment plant	-	6.58	mg/L
2	butan-1-ol	71-36-3 200-751-6		

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

	water	fresh water	0.082	mg/L
	water	marine water	0.008	mg/L
	water	Aqua intermittent	2.25	mg/L
	water	fresh water sediment	0.324	mg/kg dry weight
	water	marine water sediment	0.032	mg/kg dry weight
	soil	-	0.017	mg/kg dry weight
	sewage treatment plant	-	2476	mg/L
3	2-methoxy-1-methylethyl acetate		108-65-6 203-603-9	
	water	fresh water	0.635	mg/L
	water	marine water	0.064	mg/L
	water	fresh water sediment	3.29	mg/kg
	with reference to: dry weight			
	water	marine water sediment	0.329	mg/kg
	with reference to: dry weight			
	soil	-	0.29	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L
4	zinc oxide		1314-13-2 215-222-5	
	water	fresh water	20.6	µg/L
	with reference to: Zn			
	water	marine water	6.1	µg/L
	with reference to: Zn			
	water	fresh water sediment	117.8	mg/kg
	water	marine water sediment	56.5	mg/kg
	with reference to: Zn, dry weight			
	soil	-	35.6	mg/kg
	with reference to: Zn, dry weight			
	sewage treatment plant	-	100	µg/L
5	trizinc bis(orthophosphate)		7779-90-0 231-944-3	
	water	fresh water	20.6	µg/L
	water	marine water	6.1	µg/L
	water	fresh water sediment	117.8	mg/kg dry weight
	water	marine water sediment	56.5	mg/kg dry weight
	water	fresh water	85	µg/L
	water	marine water	42.5	µg/L
	water	fresh water sediment	867.4	mg/kg dry weight
	water	marine water sediment	957.7	mg/kg dry weight
	soil	-	35.6	mg/kg
	sewage treatment plant	-	100	µg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	In case of short-term contact / splash protection: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	120	min
Appropriate Material	In case of prolonged exposure: nitrile rubber		
Material thickness	>	0.4	mm
Breakthrough time	>	480	min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
according to product name	
Odour	
like solvents	
pH value	
No data available	
Boiling point / boiling range	
Value	> 120 °C
Reference substance	solvent mixture
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Value	24 - 26 °C
Method	closed cup
Ignition temperature	
Value	> 200 °C
Reference substance	solvent mixture
Oxidising properties	
Not applicable	

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Flammability			
Not applicable			
Lower explosion limit			
Value	>	0.6	% vol
Reference substance	solvent mixture		
Upper explosion limit			
Value	<	7.5	% vol
Reference substance	solvent mixture		
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	1.46	-	1.50 g/cm ³
Reference temperature		20	°C
Method	DIN 51757		
Solubility in water			
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Not applicable			
Source		ECHA	
2	xylene	1330-20-7	215-535-7
log Pow		3.15	
Reference temperature		20 °C	
with reference to		CAS 100-41-4	
Source		ECHA	
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow		1.2	
Reference temperature		20 °C	
Method		OECD 117	
Source		ECHA	
Kinematic viscosity			
Value	1200	-	1300 Pa*s
Reference temperature		20	°C
Method	DIN 53019		
Solvent separation test			
Value	<	3	%
Reference temperature		20	°C
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LD50	>	3492	mg/kg bodyweight
Species	rat		
Source	ECHA		
3	xylene	1330-20-7	215-535-7
LD50	3523	- 4000	mg/kg bodyweight
Species	rat		
Method	EU Method B.1		
Source	ECHA		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50		5155	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
5	zinc oxide	1314-13-2	215-222-5
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
6	ethylbenzene	100-41-4	202-849-4

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

LD50		3500	mg/kg bodyweight
Species	rat		
Source	ECHA		
7	trizinc bis(orthophosphate)	7779-90-0	231-944-3
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity (result of the ATE calculation for the mixture)

No	Product Name
1	einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LD50	>	3160	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
2	xylene	1330-20-7	215-535-7
LD50		12126	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
3	butan-1-ol	71-36-3	200-751-6
LD50	appr.	3430	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		
5	zinc oxide	1314-13-2	215-222-5
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity (result of the ATE calculation for the mixture)

No	Product Name
1	einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists)).

Acute inhalational toxicity

No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
LC50		5.09	mg/l
Duration of exposure		4	h
State of aggregation	Dust		

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LC50	>	6.193	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	xylene	1330-20-7	215-535-7
LC50		29.1	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	EU Method B.2		
Source	ECHA		
4	butan-1-ol	71-36-3	200-751-6
LC50	>	17.76	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
5	zinc oxide	1314-13-2	215-222-5
LC50	>	5.7	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
6	trizinc bis(orthophosphate)	7779-90-0	231-944-3
LC50	>	5.41	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	low-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	xylene	1330-20-7	215-535-7
Species	rat		
Source	ECHA		
Evaluation	irritant		
4	butan-1-ol	71-36-3	200-751-6
Species	rabbit		

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Source Evaluation	ECHA irritant		
5	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
6	zinc oxide	1314-13-2	215-222-5
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
7	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		

Serious eye damage/irritation

No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
3	xylene	1330-20-7	215-535-7
Species	rabbit		
Source	ECHA		
Evaluation	irritant		
4	butan-1-ol	71-36-3	200-751-6
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	strongly irritant		
5	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
6	zinc oxide	1314-13-2	215-222-5
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
7	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		

Respiratory or skin sensitisation

No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Route of exposure	Skin		
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
3	xylene	1330-20-7	215-535-7
Route of exposure	Skin		
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
5	zinc oxide	1314-13-2	215-222-5
Route of exposure	respiratory tract		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	Skin		
Species	Guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
6	trizinc bis(orthophosphate)	7779-90-0	231-944-3
Route of exposure	Skin		
Species	guinea pig		
Source	ECHA / Read across		
Evaluation	non-sensitizing		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Type of examination	In vitro mammalian cytogenicity		
Method	OECD 487		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Route of exposure	oral		
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus		
Species	rat		
Method	OECD 474		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	butan-1-ol	71-36-3	200-751-6
Source	ECHA		

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Evaluation/classification	Based on available data, the classification criteria are not met.		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type of examination	in vitro gene mutation study in bacteria		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5

Route of exposure	oral		
NOAEL	>=	1000	mg/kg bw/d
Type of examination	Reproductive studies - one generation		
Species	rat		
Method	OECD 443		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Route of exposure	oral		
NOAEL		1000	mg/kg bw/d
Type of examination	Prenatal Developmental Toxicity Study		
Species	rat		
Method	OECD 414		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

3	butan-1-ol	71-36-3	200-751-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5

Route of exposure	oral		
NOEL		7500	mg/kg bw/d
Species	mouse		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

STOT - single exposure
No data available

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5

Route of exposure	oral		
NOAEL	>	962	mg/kg bw/d
Species	rat		
Method	OECD 408		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Route of exposure	inhalational		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Route of exposure	oral
Species	rats (male/female)
Method	OECD 422
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LL50		9.2	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
2	xylene	1330-20-7	215-535-7
LC50		2.6	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
with reference to	CAS 106-42-3		
Method	OECD 203		
Source	ECHA		
3	butan-1-ol	71-36-3	200-751-6
LC50		1376	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LC50	100	- 180	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
5	ethylbenzene	100-41-4	202-849-4
LC50		5.1	mg/l
Duration of exposure		96	h
Species	Menidia menidia		
Source	ECHA		

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
NOEC	>	1.3	mg/l
Duration of exposure		56	day(s)
Species	Salmo gairdneri		
Method	OECD 210		
Source	ECHA		

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50		3.2	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	butan-1-ol	71-36-3	200-751-6
EC50		1328	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50	>	500	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	EU Method C.2		
Source	ECHA		
4	ethylbenzene	100-41-4	202-849-4
EC50		2.4	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	EPA		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	butan-1-ol	71-36-3	200-751-6
NOEC		4.1	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
NOEC	>=	100	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		
3	ethylbenzene	100-41-4	202-849-4
NOEC		0.96	mg/l
Species	Ceriodaphnia dubia		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
EC50	>	100	mg/l
Duration of exposure		72	h
Species	Raphidocelis subcapitata		

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

Method	OECD 201
Source	ECHA
Evaluation/classification	Based on the available data, the classification criteria are not met.
2	Hydrocarbons, C9, aromatics 64742-95-6 918-668-5
EL50	2.9 mg/l
Duration of exposure	72 h
Species	Pseudokirchneriella subcapitata
Method	OECD 201
Source	ECHA
3	xylene 1330-20-7 215-535-7
EC50	3.2 mg/l
Duration of exposure	72 h
Species	Pseudokirchneriella subcapitata
with reference to	CAS 106-42-3
Method	OECD 201
Source	ECHA
4	butan-1-ol 71-36-3 200-751-6
EC50	225 mg/l
Duration of exposure	72 h
Species	Pseudokirchneriella subcapitata
Method	OECD 201
Source	ECHA
5	2-methoxy-1-methylethyl acetate 108-65-6 203-603-9
EC50	> 1000 mg/l
Duration of exposure	96 h
Species	Raphidocelis subcapitata
Method	OECD 201
Source	ECHA
6	ethylbenzene 100-41-4 202-849-4
EC50	4.9 mg/l
Duration of exposure	72 h
Species	Skeletonema costatum
Source	ECHA

Toxicity to algae (chronic)
No data available

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EC50	>	99 mg/l	
Duration of exposure		10 min	
Species	activated sludge		
Method	OECD 209		
Source	ECHA		
2	butan-1-ol	71-36-3	200-751-6
EC50		4390 mg/l	
Duration of exposure		17 h	
Species	Pseudomonas putida		
Method	DIN 38412		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC10	>	1000 mg/l	
Duration of exposure		30 min	
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Source Evaluation	ECHA Not applicable for inorganic substances.		
2	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Type	BSB		
Value		78	%
Duration		28	d
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
3	xylene	1330-20-7	215-535-7
Value	>	20	%
Duration		28	day(s)
with reference to	CAS 106-42-3		
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
4	butan-1-ol	71-36-3	200-751-6
Type	DOC decrease		
Value		92	%
Duration		20	day(s)
Method	OECD		
Source	ECHA		
Evaluation	readily biodegradable		
5	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type	aerobic biodegradation		
Value		83	%
Duration		28	day(s)
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	xylene	1330-20-7	215-535-7
BCF		25.6	
Species	Oncorhynchus mykiss		
Source	ECHA		

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
Not applicable			
Source	ECHA		
2	xylene	1330-20-7	215-535-7
log Pow		3.15	
Reference temperature		20	°C
with reference to	CAS 100-41-4		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow		1.2	
Reference temperature		20	°C
Method	OECD 117		
Source	ECHA		

12.4 Mobility in soil

No data available.

Trade name: einza Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
 Classification code F1
 Packing group III
 Hazard identification no. 30
 UN number UN1263
 Proper shipping name PAINT
 Tunnel restriction code D/E
 Label 3
 Environmentally hazardous substance mark Symbol "fish and tree"

14.2 Transport IMDG

Class 3
 Packing group III
 UN number UN1263
 Proper shipping name PAINT
 Technical name Hydrocarbons, C9, aromatics
 EmS F-E+S-E
 Label 3
 Marine pollutant mark Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class 3
 Packing group III
 UN number UN1263
 Proper shipping name Paint
 Label 3

14.4 Other information

No data available.

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack

Product no.: 0071594

Current version : 7.0.0, issued: 04.01.2024

Replaced version: 6.1.1, issued: 14.03.2023

Region: GB

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40
The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	butan-1-ol	71-36-3	200-751-6	75
2	Limestone	1317-65-3	215-279-6	75
3	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight > 700 - < 1100)	25068-38-6	500-033-5	75
4	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5	75
5	toluene	108-88-3	203-625-9	75
6	xylene	1330-20-7	215-535-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5c
If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 28.29 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : j, type: lb = 500 g/l
Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

National regulations

Other national regulations

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

Trade name: einzA Lawirostal 2-K-Epoxi-Primer, weiß Stammlack**Product no.:** 0071594**Current version :** 7.0.0, issued: 04.01.2024**Replaced version:** 6.1.1, issued: 14.03.2023**Region:** GB**SECTION 16: Other information****Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H351i	Suspected of causing cancer by inhalation.
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

P	The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
V	If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.
W	It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.
1	The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653605