

Trade name: einZA mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

einZA mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
decorative paints/finishes

Uses advised against
No data available.

1.3 Details of the supplier of the safety data sheet

Address

einZA Farben GmbH & Co KG
Junkersstraße 13
30179 Hannover

Telephone no. +49 (0)511 67490-0
Fax no. +49 (0)511 67490-20
e-mail info@einZA.com

Advice on Safety Data Sheet
sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):
+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411
Flam. Liq. 3; H226
STOT SE 3; H335
STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS09

Signal word

Warning

Hazardous component(s) to be indicated on label:

Hydrocarbons, C9, aromatics

Hazard statement(s)

H226 Flammable liquid and vapour.

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
- P391 Collect spillage.
- P405 Store locked up.
- P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

- PBT assessment
The components of this product are not considered to be a PBT.
- vPvB assessment
The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Hydrocarbons, C9, aromatics		pls. refer to footnote (2)
	64742-95-6 918-668-5 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066	>= 25.00 - < 50.00 wt%
2	Reaction mass of xylene and ethylbenzene		
	- 905-588-0 - 01-2119488216-32	Acute Tox. 4; H312 Acute Tox. 4; H332 Asp. Tox. 1; H304 Eye Irrit. 2; H319 Flam. Liq. 3; H226 Skin Irrit. 2; H315 STOT RE 2; H373 STOT SE 3; H335	>= 5.00 - < 10.00 wt%
3	2-ethoxy-1-methylethyl acetate		
	54839-24-6 259-370-9 603-177-00-8 01-2119475116-39	Flam. Liq. 3; H226 STOT SE 3; H336	>= 5.00 - < 10.00 wt%
4	n-butyl acetate		
	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	< 5.00 wt%

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

5	2-methoxy-1-methylethyl acetate			
	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(2) According to the latest state of knowledge and applying the criteria set out in annex I to Regulation (EC) No 1272/2008, the aforementioned classification is required. This classification goes beyond the classification set out in table 3, Annex VI to Regulation (CE) No 1272/2008.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	P	-	-	-
2	-	STOT RE 2; H373: C >= 10%	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO2, powders, water spray

Unsuitable extinguishing media

water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); Toxic pyrolysis products; Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Is not allowed to be released into the sewerage or water courses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture. Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. Avoid inhalation of dust from sanding. For personal protection see section 8.

General protective and hygiene measures

Avoid skin and eye contact. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Comply with legal health and safety regulations; Prevent unauthorised access. Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Requirements for storage rooms and vessels

Always keep in containers of same material as the original one. Never use pressure to empty: container is not a pressure vessel. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Observe label precautions.

Incompatible products

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
List of approved workplace exposure limits (WELs) / EH40			

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Butyl acetate				
WEL short-term (15 min reference period)	966	mg/m ³	200	ppm
WEL long-term (8-hr TWA reference period)	724	mg/m ³	150	ppm
EU 2019/1831				
n-Butyl acetate				
WEL short-term (15 min reference period)	723	mg/m ³	150	ppm
WEL long-term (8-hr TWA reference period)	241	mg/m ³	50	ppm
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9	
List of approved workplace exposure limits (WELs) / EH40				
1-Methoxypropylacetate				
WEL short-term (15 min reference period)	548	mg/m ³	100	ppm
WEL long-term (8-hr TWA reference period)	274	mg/m ³	50	ppm
Comments	Sk			
2000/39/EC				
2-Methoxy-1-methylethylacetate				
WEL short-term (15 min reference period)	550	mg/m ³	100	ppm
WEL long-term (8-hr TWA reference period)	275	mg/m ³	50	ppm
Skin resorption / sensibilisation	Skin			

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C9, aromatics			64742-95-6 918-668-5	
	dermal	Long term (chronic)	systemic	12.5	mg/kg/day
	inhalative	Long term (chronic)	systemic	151	mg/m ³
2	Reaction mass of xylene and ethylbenzene			- 905-588-0	
	dermal	Long term (chronic)	systemic	212.00	mg/kg/day
	inhalative	Short term (acut)	systemic	442.00	mg/m ³
	inhalative	Short term (acut)	local	442.00	mg/m ³
	inhalative	Long term (chronic)	systemic	221.00	mg/m ³
	inhalative	Long term (chronic)	local	221.00	mg/m ³
3	2-ethoxy-1-methylethyl acetate			54839-24-6 259-370-9	
	dermal	Long term (chronic)	systemic	103	mg/kg/day
	inhalative	Long term (chronic)	systemic	152	mg/m ³
	inhalative	Short term (acut)	systemic	2366	mg/m ³
4	n-butyl acetate			123-86-4 204-658-1	
	dermal	Long term (chronic)	systemic	11	mg/kg/day
	dermal	Short term (acut)	systemic	11	mg/kg/day
	inhalative	Long term (chronic)	systemic	300	mg/m ³
	inhalative	Short term (acut)	systemic	600	mg/m ³
	inhalative	Long term (chronic)	local	300	mg/m ³
	inhalative	Short term (acut)	local	600	mg/m ³
5	2-methoxy-1-methylethyl acetate			108-65-6 203-603-9	
	dermal	Long term (chronic)	systemic	796	mg/kg/day
	inhalative	Long term (chronic)	systemic	275	mg/m ³
	inhalative	Short term (acut)	local	550	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C9, aromatics			64742-95-6 918-668-5	
	oral	Long term (chronic)	systemic	7.5	mg/kg/day
	dermal	Long term (chronic)	systemic	7.5	mg/kg/day

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

	inhalative	Long term (chronic)	systemic	32	mg/m ³
2	Reaction mass of xylene and ethylbenzene			-	905-588-0
	oral	Long term (chronic)	systemic	12.50	mg/kg/day
	dermal	Long term (chronic)	systemic	125.00	mg/kg/day
	inhalative	Short term (acut)	systemic	260.00	mg/m ³
	inhalative	Long term (chronic)	systemic	65.30	mg/m ³
	inhalative	Short term (acut)	local	260.00	mg/m ³
	inhalative	Long term (chronic)	local	65.30	mg/m ³
3	2-ethoxy-1-methylethyl acetate			54839-24-6	259-370-9
	oral	Long term (chronic)	systemic	13.1	mg/kg/day
	dermal	Long term (chronic)	systemic	62	mg/kg/day
	inhalative	Long term (chronic)	systemic	181	mg/m ³
	inhalative	Short term (acut)	systemic	1420	mg/m ³
4	n-butyl acetate			123-86-4	204-658-1
	oral	Long term (chronic)	systemic	2	mg/kg/day
	oral	Short term (acut)	systemic	2	mg/kg/day
	dermal	Long term (chronic)	systemic	6	mg/kg/day
	dermal	Short term (acut)	systemic	6	mg/kg/day
	inhalative	Long term (chronic)	systemic	35.7	mg/m ³
	inhalative	Short term (acut)	systemic	300	mg/m ³
	inhalative	Long term (chronic)	local	35.7	mg/m ³
	inhalative	Short term (acut)	local	300	mg/m ³
5	2-methoxy-1-methylethyl acetate			108-65-6	203-603-9
	oral	Long term (chronic)	systemic	36	mg/kg/day
	oral	Short term (acut)	systemic	500	mg/kg/day
	dermal	Long term (chronic)	systemic	320	mg/kg/day
	inhalative	Long term (chronic)	systemic	33	mg/m ³
	inhalative	Long term (chronic)	local	33	mg/m ³

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	Reaction mass of xylene and ethylbenzene		-
			905-588-0
	water	fresh water	0.327 mg/L
	water	marine water	0.327 mg/L
	water	fresh water sediment	12.46 mg/kg
	water	marine water sediment	12.46 mg/kg
	soil	-	2.31 mg/kg
	sewage treatment plant	-	6.58 mg/L
2	2-ethoxy-1-methylethyl acetate		54839-24-6
			259-370-9
	water	fresh water	2 mg/L
	water	marine water	0.2 mg/L
	water	Aqua intermittent	2 mg/L
	water	fresh water sediment	8.2 mg/kg dry weight
	water	marine water sediment	0.82 mg/kg dry weight
	soil	-	0.67 mg/kg dry weight
	sewage treatment plant	-	62.5 mg/L
	secondary poisoning	-	117 mg/kg food
3	n-butyl acetate		123-86-4
			204-658-1
	water	fresh water	0.18 mg/L
	water	marine water	0.018 mg/L

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

	water	Aqua intermittent	0.36	mg/L
	water	fresh water sediment	0.981	mg/kg dry weight
	water	marine water sediment	0.0981	mg/kg dry weight
	soil	-	0.0903	mg/kg
	sewage treatment plant	-	35.6	mg/L
4	2-methoxy-1-methylethyl acetate		108-65-6 203-603-9	
	water	fresh water	0.635	mg/L
	water	marine water	0.064	mg/L
	water	fresh water sediment	3.29	mg/kg
	with reference to: dry weight			
	water	marine water sediment	0.329	mg/kg
	with reference to: dry weight			
	soil	-	0.29	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	100	mg/L

8.2 Exposure controls

Appropriate engineering controls

Provide good ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. In case of brush application: Filter A2. When applied by spraying: Filter A2P2. (DIN EN 14387)

Eye / face protection

Wear safety goggles to protect against splashes. Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 120 min

Appropriate Material In case of prolonged exposure: nitrile rubber

Material thickness > 0.4 mm

Breakthrough time > 480 min

Other

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation

liquid

Form

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

liquid			
Colour			
according to product name			
Odour			
like solvents			
pH value			
No data available			
Boiling point / boiling range			
Value	>	120	°C
Reference substance	solvent mixture		
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value	40	- 42	°C
Method	closed cup		
Ignition temperature			
Value	>	200	°C
Reference substance	solvent mixture		
Oxidising properties			
Not applicable			
Flammability			
Not applicable			
Lower explosion limit			
Value	>	0.6	% vol
Reference substance	solvent mixture		
Upper explosion limit			
Value	<	7.5	% vol
Reference substance	solvent mixture		
Vapour pressure			
Value	<	100	hPa
Reference temperature		50	°C
Reference substance	solvent mixture		
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value	1.17	- 1.22	g/cm ³
Reference temperature		20	°C
Method	DIN 51757		
Solubility in water			
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

log Pow	0.76	
Reference temperature	22	°C
with reference to	pH 7	
Source	ECHA	
2	n-butyl acetate	123-86-4 204-658-1
log Pow	2.3	
Reference temperature	25	°C
Method	OECD 117	
Source	ECHA	
3	2-methoxy-1-methylethyl acetate	108-65-6 203-603-9
log Pow	1.2	
Reference temperature	20	°C
Method	OECD 117	
Source	ECHA	

Kinematic viscosity			
Value	40	- 55	sec
Reference temperature		20	°C
Method	DIN EN 2431 (6 mm)		

Solvent separation test			
Value	<	3	%
Reference temperature		20	°C

Particle characteristics			
No data available			

9.2 Other information

Other information			
No data available.			

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions (See section 7).

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LD50	>	3492	mg/kg bodyweight
Species	rat		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LD50		10760	mg/kg bodyweight
Species	rat		
Method	OECD 423		

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50		5155	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LD50	>	3160	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
LD50	>	14112	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 402		
Source	ECHA		

Acute inhalational toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LC50	>	6.193	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
LC50	>	6.99	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Evaluation/classification	Based on available data, the classification criteria are not met.
---------------------------	---

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Species		rabbit	
Method		OECD 404	
Source		ECHA	
Evaluation		low-irritant	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Duration of exposure		4	h
Species		rabbit	
Method		OECD 404	
Source		ECHA	
Evaluation		non-irritant	
Evaluation/classification		Based on available data, the classification criteria are not met.	
3	n-butyl acetate	123-86-4	204-658-1
Species		rabbit	
Method		OECD 404	
Source		ECHA	
Evaluation		non-irritant	
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species		rabbit	
Method		OECD 404	
Source		ECHA	
Evaluation		non-irritant	

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
Evaluation/classification		Based on available data, the classification criteria are not met.	
3	n-butyl acetate	123-86-4	204-658-1
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		non-irritant	

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA	
Evaluation		non-sensitizing	
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Route of exposure		Skin	
Species		guinea pig	

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing
Evaluation/classification	Based on available data, the classification criteria are not met.
3	2-methoxy-1-methylethyl acetate 108-65-6 203-603-9
Route of exposure	Skin
Species	guinea pig
Method	OECD 406
Source	ECHA
Evaluation	non-sensitizing

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type of examination	in vitro gene mutation study in bacteria		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	n-butyl acetate	123-86-4	204-658-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No data available			

STOT - single exposure			
No data available			

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Route of exposure	dermal		
Duration of exposure	3		months
Species	rabbit		
Method	OECD 411		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are met.		
2	n-butyl acetate	123-86-4	204-658-1
Route of exposure	inhalational		
NOAEC	500		ppm
Duration of exposure	90		day(s)
Species	rat		
Method	EPA OTS 798.2450		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Route of exposure	oral
Species	rats (male/female)
Method	OECD 422
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Aspiration hazard
No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
LL50		9.2	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
LC50		140	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
LC50		18	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
LC50	100	- 180	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)
No data available

Toxicity to Daphnia (acute)

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50		3.2	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
EC50		110	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	n-butyl acetate	123-86-4	204-658-1
EC50		44	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50	>	500	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	EU Method C.2		
Source	ECHA		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
NOEC		23	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
with reference to	CAS 110-19-0		
Method	OECD 211		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
NOEC	>=	100	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EL50		2.9	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
EC50	>	100	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Method	OECD 201		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC50	>	1000	mg/l
Duration of exposure		96	h

Trade name: einzA mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Species	Raphidocelis subcapitata
Method	OECD 201
Source	ECHA

Toxicity to algae (chronic)
No data available

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
EC50	>	99	mg/l
Duration of exposure		10	min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		
2	n-butyl acetate	123-86-4	204-658-1
IC50		356	mg/l
Duration of exposure		40	h
Species	Tetrahymena pyriformis (Protozoa)		
Source	ECHA		
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
EC10	>	1000	mg/l
Duration of exposure		30	min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C9, aromatics	64742-95-6	918-668-5
Type	BSB		
Value		78	%
Duration		28	d
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
2	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
Type	aerobic biodegradation		
Value		100	%
Duration		28	d
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
3	n-butyl acetate	123-86-4	204-658-1
Type	aerobic biodegradation		
Value		83	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
4	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
Type	aerobic biodegradation		
Value		83	%
Duration		28	day(s)
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		

Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
Type	Photolysis		

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Half-life	3.3	day(s)
Reference temperature	25	°C
Source	ECHA	

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	n-butyl acetate	123-86-4	204-658-1
BCF		15.3	
Method		Calculation model used (Q)SAR	
Source		ECHA	

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	2-ethoxy-1-methylethyl acetate	54839-24-6	259-370-9
log Pow		0.76	
Reference temperature		22 °C	
with reference to		pH 7	
Source		ECHA	
2	n-butyl acetate	123-86-4	204-658-1
log Pow		2.3	
Reference temperature		25 °C	
Method		OECD 117	
Source		ECHA	
3	2-methoxy-1-methylethyl acetate	108-65-6	203-603-9
log Pow		1.2	
Reference temperature		20 °C	
Method		OECD 117	
Source		ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not allow to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company. Disposal of the product should be carried out in accordance with all applicable regulations following consultation with the responsible local authority and the disposal company in an authorised and suitable disposal facility.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers must be scrapped or reconditioned.

Trade name: einza mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	III
Hazard identification no.	30
UN number	UN1263
Proper shipping name	PAINT
Tunnel restriction code	D/E
Label	3
Environmentally hazardous substance mark	Symbol "fish and tree"

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	PAINT
Technical name	Hydrocarbons, C9, aromatics
EmS	F-E+S-E
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

Trade name: einzA mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

No	Substance name	CAS no.	EC no.	No
1	1,2,4-trimethylbenzene	95-63-6	202-436-9	75
2	2-methylpropan-1-ol	78-83-1	201-148-0	75
3	Cumene	98-82-8	202-704-5	75
4	xylene	1330-20-7	215-535-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

E2, P5c

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content

47.76 %

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

relevant VOC limit value as referred to in Annex II of Directive 2004/42/CE , Cat. : j, type: lb = 500 g/l

Max. VOC content (limit value) of the product in its ready for use condition = < 500 g/l

National regulations**Other national regulations**

Adhere to national regulations for proper handling and use of hazardous materials. Use appropriate personal protective equipment.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

P	The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
---	--

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Trade name: einZA mix Lawidur hgl 2K-PU-Buntlack, Basis 3 Stammlack

Product no.: 0071309

Current version : 3.3.0, issued: 03.01.2024

Replaced version: 3.2.2, issued: 03.07.2023

Region: GB

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 653578